Marine and Land Based VHF Antenna. Tx/Rx. 150W RAL9005 Black. 0 dBd. UHF female. N239F. Packed in a tube

This is an omnidirectional dipole antenna manufactured in premium quality materials in order to prevent galvanic corrosion. Radiating elements are made of brass. The antenna is manufactured using crimping technology giving the antenna a 4-5 times stronger build-up. The antenna is always subject for improvement. The antenna has the same rugged design as all other AC Antennas products thus it withstands harsh environmental conditions, both on Sea and Land.


Short description	
Product group	VHF
Design	Coaxial dipole
Pattern	Omnidirectional
Electrical specifications	
Frequency range [MHz]	146.0-162.5
Bandwidth [MHz]	16.5
Nominal Impedance [Ohm]	50
Max. Input Power [Watt]	150
Gain [dBd/dBi/Marine dB]	0 / 2.15 / 3
VSWR	<1.5:1
Polarisation	Vertical
DC Shorted	Yes
DC Grounded	Yes
Connector	UHF-Female
Mechanical specifications	
Length [m/ft]	1.26 / 4.14
Sections	1
Weight [kg/lbs]	0.50 / 1.10
Survival Wind Speed [km/h / m/s / mph]	200 / 55 / 124
Wind Area [m2/ft2]	0.0186 / 0.2002
Wind Load @ 160km/h [N]	27
Material	Fibreglass
Colour	Black
Operating Temperature Range [°C/°F]	-55 to +70 / -67 to +158
Ingress Protection	IP68
Thread	1" 14TPI male / ISO 228/1-G1 female
Mounting	Mounting nut included
5	v





AC Antennas A/S | Fabriksparken 40, DK-2600 Glostrup, Denmark Phone: +45 4581 0413 | acantennas@acantennas.com | www.acantennas.com





AC Antennas A/S | Fabriksparken 40, DK-2600 Glostrup, Denmark Phone: +45 4581 0413 | acantennas@acantennas.com | www.acantennas.com



Specifications subject to change without further notice. The information in this document does not form part of any quotation or contract