

PRODUCT BASIC INFORMATION

OCEANLINK NAVIGATION WIND ANGLE GAUGE

Best Performance in Outdoor Environments



OCEANLINK CLASSIC NAVIGATION

ART NR: A2C1957400001

Precision CAN Instrumentation for Leisure Boats

KEY FEATURES

- NMEA 2000
- Anti-fog double layer plastic lens
- Protection rating IP X7
- Internal calculation of true wind data

The OceanLink Navigation product family consists of five high-quality gauges with a classic analog design and modern digital bus inputs. Compatible with the NMEA 2000® protocol standard, these products can be easily integrated into your vessel's system and can read information from any NMEA 2000® compatible sensor.

The OceanLink Wind Angle Gauge displays the Apparent Wind Angle (AWA) or True Wind Angle (TWA). Switch between the two by activating the infrared push button conveniently located on the instrument's dial.

The true wind data can be received from the digital network but can also be calculated on the gauge internally, given the SOG and COG information is available.





TECHNICAL DATA

Housing	Material: PC-FR	
Bezel	Material: PC-FR (Black)	
Operating Temperature	-20°C to 70°C	
Storage Temperature	-40°C to 85°C	
Operating Voltage	12 VDC (Provided by NMEA Backbone)	
Protection Class	IEC60945 exposed equipment IP X7 front and rear	
Approval	CE, UKCA, RoHS, NMEA2000®	
Data Input	NMEA2000	















CONNECTOR

M12-5Pin

Pin	Signal
1	Shield
2	Power (12V)
3	GND
4	CAN-High
5	CAN-Low





NMEA 2000 MESSAGES

Description	PGN
Wind Data	130306
COG & SOG, Rapid Update	129026



Veratron AG / English © 2024